



注記

1. 材質：JIS G 5705 FCMB 275-5
2. ねじ：JIS B 0203 管用テーパねじ
3. 表面处理：熔融亜鉛めっき
4. 形状寸法：JIS B 2301に準拠，※は当社標準寸法
5. ○印は、受注生産品です

単位：mm

呼び ①×②×③	D ₁ (参考)	ねじ部		h ₁ (参考)	D ₂ (参考)	ねじ部		h ₂ (参考)	t (参考)	A	B
		d ₁ ねじ	φ ₁ (参考)			d ₂ ねじ	φ ₂ (参考)				
3/4×3/4×1/2	3.6	Rc 3/4	1.3	6	3.0	Rc 1/2	1.1	6	3.0	2.9	3.0
1×1×1/2	4.4	Rc 1	1.5	7	3.0	Rc 1/2	1.1	6	3.0	3.2	3.3
1×1×3/4	4.4	Rc 1	1.5	7	3.6	Rc 3/4	1.3	6	3.0	3.4	3.5
1 1/4×1 1/4×1/2	5.3	Rc 1 1/4	1.7	8	3.0	Rc 1/2	1.1	6	3.5	3.4	3.8
1 1/4×1 1/4×3/4	5.3	Rc 1 1/4	1.7	8	3.6	Rc 3/4	1.3	6	3.5	3.8	4.0
1 1/4×1 1/4×1	5.3	Rc 1 1/4	1.7	8	4.4	Rc 1	1.5	7	3.5	4.0	4.2
1 1/2×1 1/2×1/2	6.0	Rc 1 1/2	1.8	9	3.0	Rc 1/2	1.1	6	3.5	3.5	4.2
1 1/2×1 1/2×3/4	6.0	Rc 1 1/2	1.8	9	3.6	Rc 3/4	1.3	6	3.5	3.8	4.3
1 1/2×1 1/2×1	6.0	Rc 1 1/2	1.8	9	4.4	Rc 1	1.5	7	3.5	4.1	4.5
1 1/2×1 1/2×1 1/4	6.0	Rc 1 1/2	1.8	9	5.3	Rc 1 1/4	1.7	8	3.5	4.5	4.8
2×2×1/2	7.3	Rc 2	2.0	11	3.0	Rc 1/2	1.1	6	4.0	3.8	4.8
2×2×3/4	7.3	Rc 2	2.0	11	3.6	Rc 3/4	1.3	6	4.0	4.1	4.9
2×2×1	7.3	Rc 2	2.0	11	4.4	Rc 1	1.5	7	4.0	4.4	5.1
2×2×1 1/4	7.3	Rc 2	2.0	11	5.3	Rc 1 1/4	1.7	8	4.0	4.8	5.4
2×2×1 1/2	7.3	Rc 2	2.0	11	6.0	Rc 1 1/2	1.8	9	4.0	5.2	5.5
2 1/2×2 1/2×1/2	9.1	Rc 2 1/2	2.3	12	3.0	Rc 1/2	1.1	6	4.5	4.1	5.7
2 1/2×2 1/2×3/4	9.1	Rc 2 1/2	2.3	12	3.6	Rc 3/4	1.3	6	4.5	4.4	5.8
2 1/2×2 1/2×1	9.1	Rc 2 1/2	2.3	12	4.4	Rc 1	1.5	7	4.5	4.8	6.0
2 1/2×2 1/2×1 1/4	9.1	Rc 2 1/2	2.3	12	5.3	Rc 1 1/4	1.7	8	4.5	5.2	6.2
2 1/2×2 1/2×1 1/2	9.1	Rc 2 1/2	2.3	12	6.0	Rc 1 1/2	1.8	9	4.5	5.5	6.2
2 1/2×2 1/2×2	9.1	Rc 2 1/2	2.3	12	7.3	Rc 2	2.0	11	4.5	6.0	6.5

単位：mm

呼び ①×②×③	D ₁ (参考)	ねじ部		h ₁ (参考)	D ₂ (参考)	ねじ部		h ₂ (参考)	t (参考)	A	B
		d ₁ ねじ	φ ₁ (参考)			d ₂ ねじ	φ ₂ (参考)				
※3×3×1/2	10.5	Rc 3	2.5	13	3.0	Rc 1/2	1.1	6	5.0	4.3	6.5
3×3×3/4	10.5	Rc 3	2.5	13	3.6	Rc 3/4	1.3	6	5.0	4.6	6.6
3×3×1	10.5	Rc 3	2.5	13	4.4	Rc 1	1.5	7	5.0	5.0	6.8
3×3×1 1/4	10.5	Rc 3	2.5	13	5.3	Rc 1 1/4	1.7	8	5.0	5.5	7.0
3×3×1 1/2	10.5	Rc 3	2.5	13	6.0	Rc 1 1/2	1.8	9	5.0	5.8	7.2
3×3×2	10.5	Rc 3	2.5	13	7.3	Rc 2	2.0	11	5.0	6.2	7.2
3×3×2 1/2	10.5	Rc 3	2.5	13	9.1	Rc 2 1/2	2.3	12	5.0	7.2	7.5
※4×4×1/2	13.3	Rc 4	2.8	16	3.0	Rc 1/2	1.1	6	6.0	5.0	7.9
4×4×3/4	13.3	Rc 4	2.8	16	3.6	Rc 3/4	1.3	6	6.0	5.4	8.0
4×4×1	13.3	Rc 4	2.8	16	4.4	Rc 1	1.5	7	6.0	5.7	8.3
4×4×1 1/4	13.3	Rc 4	2.8	16	5.3	Rc 1 1/4	1.7	8	6.0	6.1	8.6
4×4×1 1/2	13.3	Rc 4	2.8	16	6.0	Rc 1 1/2	1.8	9	6.0	6.3	8.6
4×4×2	13.3	Rc 4	2.8	16	7.3	Rc 2	2.0	11	6.0	6.9	8.7
4×4×2 1/2	13.3	Rc 4	2.8	16	9.1	Rc 2 1/2	2.3	12	6.0	7.8	9.0
4×4×3	13.3	Rc 4	2.8	16	10.5	Rc 3	2.5	13	6.0	8.3	9.1
○5×5×3/4	16.1	Rc 5	3.0	18	3.6	Rc 3/4	1.3	6	6.5	5.5	9.6
○5×5×1	16.1	Rc 5	3.0	18	4.4	Rc 1	1.5	7	6.5	6.0	9.7
○5×5×1 1/4	16.1	Rc 5	3.0	18	5.3	Rc 1 1/4	1.7	8	6.5	6.2	10.0
○5×5×1 1/2	16.1	Rc 5	3.0	18	6.0	Rc 1 1/2	1.8	9	6.5	6.6	10.0
○5×5×2	16.1	Rc 5	3.0	18	7.3	Rc 2	2.0	11	6.5	7.2	10.3
○5×5×2 1/2	16.1	Rc 5	3.0	18	9.1	Rc 2 1/2	2.3	12	6.5	8.1	10.5
○5×5×3	16.1	Rc 5	3.0	18	10.5	Rc 3	2.5	13	6.5	8.7	10.7
○5×5×4	16.1	Rc 5	3.0	18	13.3	Rc 4	2.8	16	6.5	10.0	11.1
○6×6×1	18.9	Rc 6	3.3	20	4.4	Rc 1	1.5	7	7.5	6.4	11.0
○6×6×1 1/4	18.9	Rc 6	3.3	20	5.3	Rc 1 1/4	1.7	8	7.5	6.7	11.3
○6×6×1 1/2	18.9	Rc 6	3.3	20	6.0	Rc 1 1/2	1.8	9	7.5	7.0	11.5
○6×6×2	18.9	Rc 6	3.3	20	7.3	Rc 2	2.0	11	7.5	7.5	11.6
○6×6×2 1/2	18.9	Rc 6	3.3	20	9.1	Rc 2 1/2	2.3	12	7.5	8.5	11.8
○6×6×3	18.9	Rc 6	3.3	20	10.5	Rc 3	2.5	13	7.5	9.2	12.0
○6×6×4	18.9	Rc 6	3.3	20	13.3	Rc 4	2.8	16	7.5	10.2	12.5
○6×6×5	18.9	Rc 6	3.3	20	16.1	Rc 5	3.0	18	7.5	11.6	12.8

品名	WS継手 径違いT (バンド付)		
略号	WS-BRT	年月日	2024-8-1
桑名金属工業株式会社		図番	W86-25105