



単位：mm

呼び	ねじの呼び Rc × Rc' ◇	A◇	L	L'	L ₁	L ₂	L ₃	φD ₁	φD ₂	φD ₃	φD ₄	φD ₁ '	φD ₂ '	φD ₃ '	φD ₄ '	t ₁	t ₂
2 1/2 × 2	Rc 2 1/2 × Rc 2	65	27	26	5.6	8.9	2	78.3	84.9	91	86	62.7	68.1	73	69	4.5	4
3 × 1	Rc 3 × Rc 1	72	30	25	8.2	8.7	2	91.0	97.8	105	99	36.3	42.1	44	41	5	3
3 × 1 1/4	Rc 3 × Rc 1 1/4	72	30	25	8.2	8.7	2	91.0	97.8	105	99	45.0	50.8	53	50	5	3.5
3 × 1 1/2	Rc 3 × Rc 1 1/2	72	30	25	8.2	8.7	2	91.0	97.8	105	99	51.0	56.7	60	56	5	3.5
3 × 2	Rc 3 × Rc 2	72	30	26	8.2	8.9	2	91.0	97.8	105	99	62.7	68.1	73	69	5	4
3 × 2 1/2	Rc 3 × Rc 2 1/2	72	30	27	8.2	5.6	2	91.0	97.8	105	99	78.3	84.9	91	86	5	4.5
4 × 3	Rc 4 × Rc 3	85	33	30	9.2	8.2	3	116.2	123.2	133	127	91.0	97.8	105	99	6	5

- 備考
- 樹脂被覆色 アイボリー色
 - ◇を除く寸法は参考寸法です

品名	外面樹脂被覆継手 PC継手(ねじ込み式) 径違いソケット(バンド付)		
略号	BRS	年月日	2024-8-1
桑名金属工業株式会社		図番	G16-25050